Kap Surface Wall Ø 100

03.5733.ASB - Brushed Aluminium/Black

Luminaire for wall mounting with led light source. nonregulable 110/240V, 50-60hz power supply integrated in luminaire body.



Main specifications

Number of heads	1	**CRI**	80
Lamp category	LED	**Net lumen (lm)**	413
Power (W)	9W	**Mountings**	Wall surface
System power (W)	11W	**Environment**	Indoor dry location
CCT (K)	3000K		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	28
Beam angle C90-270 (°)	28



Luminous flux luminaire
413 lm (EXTREME CUT OFF)

Beam Angle: 28°

h(m)	E(lx)	D(m)
1	1435	0.51
2	359	1.02
3	159	1.52
4	90	2.03
5	57	2.54

Electrical

Frequency (Hz)	50/60	**Emergency**	Without
Voltage (V)	110/240	**Insulation class**	I
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		

Physical

Color	Brushed Aluminium/Black
Orientation	Fixed
Weight (kg)	1.58
Spot diameter (mm)	100
Length (mm)	100