


## Kap Surface Wall Ø100

03.5730.ASB - Brushed Aluminium/White

Luminaire for wall mounting with led light source. nonregulable 110/240V, 50-60hz power supply integrated in luminaire body.




### Main specifications

<b>Number of heads</b>	1	<b>CRI</b>	90
<b>Lamp category</b>	LED	<b>Net lumen (lm)</b>	550
<b>Power (W)</b>	9W	<b>Mountings</b>	Wall surface
<b>System power (W)</b>	11W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	3000K		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Flood
<b>Beam angle (°)</b>	29
<b>Beam angle C90-270 (°)</b>	29



Beam Angle: 29°

h(m)	E(lx)	D(m)
1	1482	0.52
2	371	1.04
3	165	1.56
4	93	2.08
5	59	2.61

Luminous flux luminaire  
550 lm (EXTREME CUT OFF)

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	110/240	<b>Insulation class</b>	I
<b>Dimmable</b>	No		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Electronic		

### Physical

<b>Color</b>	Brushed Aluminium/White
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	1.58
<b>Spot diameter (mm)</b>	100
<b>Length (mm)</b>	100

### Certification / Marking

