


Kap Surface Wall Ø100

03.5732.11B - White/Blue

Luminaire for wall mounting with led light source. nonregulable 110/240V, 50-60hz power supply integrated in luminaire body.

Luminaire for wall mounting with led light source. nonregulable 110/240V, 50-60hz power supply integrated in luminaire body.




Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	417
Power (W)	9W	Mountings	Wall surface
System power (W)	11W	Environment	Indoor
CCT (K)	3000K		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	28
Beam angle C90-270 (°)	28




Beam Angle: 28°		
h(m)	E(lx)	D(m)
1	1448	0.51
2	362	1.02
3	161	1.52
4	91	2.03
5	58	2.54

Luminous flux luminaire
417 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	110/240	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Electronic		

Certification / Marking



Physical

Color	White/Blue
Orientation	Fixed
Weight (kg)	1.58
Spot diameter (mm)	100
Length (mm)	100