



Kap Suspension Ø 100

03.5813.ANB - Black/Black


Hanging luminaire for mounting in ceiling with led light source. non-regulable 110/240V, 50/60hz power supply integrated in luminaire body.

Main specifications

| | | | |
|------------------|-------|----------------|---------------------|
| Number of heads | 1 | CRI | 80 |
| Lamp category | LED | Net lumen (lm) | 413 |
| Power (W) | 9W | Mountings | Suspension |
| System power (W) | 11W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |

Optical

| | |
|------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Flood |
| Beam angle (°) | 28 |
| Beam angle C90-270 (°) | 28 |



Beam Angle: 28°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 1435 | 0.51 |
| 2 | 359 | 1.02 |
| 3 | 159 | 1.52 |
| 4 | 90 | 2.03 |
| 5 | 57 | 2.54 |

Luminous flux luminaire
413 lm (EXTREME CUT OFF)



Electrical

| | | | |
|----------------|--------------|------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 110/240 | Insulation class | I |
| Dimmable | No | | |
| Driver | Integrated | | |
| Driver type | Non Dimmable | | |

Physical

| | |
|--------------------|-------------|
| Color | Black/Black |
| Weight (kg) | 2.27 |
| Spot diameter (mm) | 100 |
| Length (mm) | 100 |

