

## Kap Suspension Ø100

● 03.5811.ASB - Brushed Aluminium/Gold


Hanging luminaire for mounting in ceiling with led light source. non-regulable 110/240V, 50/60hz power supply integrated in luminaire body.

### Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	498
Power (W)	9W	Mountings	Suspension
System power (W)	11W	Environment	Indoor
CCT (K)	3000K		

### Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	29
Beam angle C90-270 (°)	29



Beam Angle:	29°	
	h(m)	E(lx) D(m)
	1	1485 0.52
	2	371 1.05
	3	165 1.57
	4	93 2.09
	5	59 2.62

Luminous flux luminaire  
498 lm (EXTREME CUT OFF)

### Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	110/240	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Electronic		

### Physical

Color	Brushed Aluminium/Gold
Weight (kg)	2.27
Spot diameter (mm)	100
Length (mm)	100

### Certification / Marking

