

## Kap Suspension Ø100

03.5812.11B - White/Blue

Hanging luminaire for mounting in ceiling with led light source. non-regulable 110/240V, 50/60hz power supply integrated in luminaire body.


Hanging luminaire for mounting in ceiling with led light source. non-regulable 110/240V, 50/60hz power supply integrated in luminaire body.

### Main specifications

<b>Number of heads</b>	1	<b>CRI</b>	90
<b>Lamp category</b>	LED	<b>Net lumen (lm)</b>	417
<b>Power (W)</b>	9W	<b>Mountings</b>	Suspension
<b>System power (W)</b>	11W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	3000K		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Flood
<b>Beam angle (°)</b>	28
<b>Beam angle C90-270 (°)</b>	28



Beam Angle: 28°

h(m)	E(lx)	D(m)
1	1448	0.51
2	362	1.02
3	161	1.52
4	91	2.03
5	58	2.54

Luminous flux luminaire  
417 lm (EXTREME CUT OFF)

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	110/240	<b>Insulation class</b>	I
<b>Dimmable</b>	No		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Electronic		

### Physical

<b>Color</b>	White/Blue
<b>Weight (kg)</b>	2.27
<b>Spot diameter (mm)</b>	100
<b>Length (mm)</b>	100

### Certification / Marking

