

**LED Squad 125 mm**■ **03.3960.29B - Anodized Aluminium**


Direct/indirect lighting wall luminaire with LED. Remote transformer not included. Dimmable.

**Main specifications**

<b>Lamp category</b>	LED	<b>Mountings</b>	Surface
<b>Power (W)</b>	3.2W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		
<b>Net lumen (lm)</b>	193		


**Optical**

<b>Lighting type</b>	Indirect, Direct
<b>LED type</b>	Top LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Diffused light
<b>Beam angle (°)</b>	86
<b>Beam angle C90-270 (°)</b>	99



Beam Angle: 86°

h(m)	E(lx)	D(m)
1	89	1.88
2	22	3.76
3	10	5.64
4	6	7.52
5	4	9.40

Luminous flux luminaire  
193 lm**Electrical**


<b>Voltage (V)</b>	24.00	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote excluded		
<b>Driver type</b>	Dimmable		
<b>Emergency</b>	Without		

**Physical**

<b>Color</b>	Anodized Aluminium
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	0.045
<b>Length (mm)</b>	125

**Note**

7 LEDs. Installation cables included: power cable 500 mm, connection cable 60 mm



## LED Squad 125 mm



---

Dimmable 1-10V control unit with 1 channel for 24V LED modules. Max. 120W – 5A  
60.8640



---

Dimmable DALI control unit with 1 channel for 24V LED modules. Power supply not included  
60.8635



---

Electronic transformer with constant voltage (24V) for LED. 100/240V. 60W  
60.9089



---

Electronic transformer with constant voltage (24V) for LED. 100/240V. 25W  
60.8703