


LED Squad Mini 1118 mm

03.4065.29 - Anodized Aluminium



Luminary for surface installation with LED light source. Composed of an extruded aluminum profile to which LED linear modules are incorporated. Invisible dots with continuous light. It has a fast connector in order to join modules of different lengths without wiring. It has a magnetic fixing system on metal surfaces or brackets to screw on...

Luminary for surface installation with LED light source. Composed of an extruded aluminum profile to which LED linear modules are incorporated. Invisible dots with continuous light. It has a fast connector in order to join modules of different lengths without wiring. It has a magnetic fixing system on metal surfaces or brackets to screw on conventional surfaces.




Main specifications

Lamp category	LED	Mountings	Surface
Power (W)	17.6W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		
Net lumen (lm)	1136		

Optical

Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	88
Beam angle C90-270 (°)	99



Beam Angle: 88°

h(m)	E(lx)	D(m)
1	505	1.94
2	126	3.88
3	56	5.82
4	32	7.76
5	20	9.70

Luminous flux luminaire
1136 lm

Electrical

Voltage (V)	24.00	Insulation class	III
Dimmable	No		
Driver	Remote excluded		
Driver type	Non Dimmable		
Emergency	Without		

Physical

Color	Anodized Aluminium
Orientation	Fixed
Weight (kg)	0.194
Length (mm)	1119

Note

Installation cables and driver not included. To be ordered separately. Not compatible with spots. Non dimmable.



LED Squad Mini 1118 mm



Feed cable 2500 mm
06.0097.00



Electronic transformer with constant
voltage (24V) for LED. 100/240V. 25W
60.8703



Electronic transformer with constant
voltage (24V) for LED. 100/240V. 60W
60.9089



Connection cable 150 mm
06.0098.00