


LED Squad Mini 193 mm

■ 03.4061.29 - Anodized Aluminium



Luminary for surface installation with LED light source. Composed of an extruded aluminum profile to which LED linear modules are incorporated. Invisible dots with continuous light. It has a fast connector in order to join modules of different lengths without wiring. It has a magnetic fixing system on metal surfaces or brackets to screw on...

Luminary for surface installation with LED light source. Composed of an extruded aluminum profile to which LED linear modules are incorporated. Invisible dots with continuous light. It has a fast connector in order to join modules of different lengths without wiring. It has a magnetic fixing system on metal surfaces or brackets to screw on conventional surfaces.




Main specifications

Lamp category	LED	Mountings	Surface
Power (W)	2.9W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		
Net lumen (lm)	189		

Optical

Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	88
Beam angle C90-270 (°)	99



Beam Angle: 106°

h(m)	E(lx)	D(m)
1	70	2.67
2	18	5.35
3	8	8.02
4	4	10.70
5	3	13.37

Luminous flux luminaire
189 lm

Electrical


Voltage (V)	24.00	Insulation class	III
Dimmable	No		
Driver	Remote excluded		
Driver type	Non Dimmable		
Emergency	Without		

Physical

Color	Anodized Aluminium
Orientation	Fixed
Weight (kg)	0.037
Length (mm)	193

Note

Installation cables and driver not included. To be ordered separately. Not compatible with spots. Non dimmable.



LED Squad Mini 193 mm



Electronic transformer with constant voltage (24V) for LED. 100/240V. 60W
60.9089



Feed cable 2500 mm
06.0097.00



Connection cable 150 mm
06.0098.00



Electronic transformer with constant voltage (24V) for LED. 100/240V. 25W
60.8703