


## LED Squad Mini 563 mm

### 03.4063.29 - Anodized Aluminium



Luminary for surface installation with LED light source. Composed of an extruded aluminum profile to which LED linear modules are incorporated. Invisible dots with continuous light. It has a fast connector in order to join modules of different lengths without wiring. It has a magnetic fixing system on metal surfaces or brackets to screw on...

Luminary for surface installation with LED light source. Composed of an extruded aluminum profile to which LED linear modules are incorporated. Invisible dots with continuous light. It has a fast connector in order to join modules of different lengths without wiring. It has a magnetic fixing system on metal surfaces or brackets to screw on conventional surfaces.




### Main specifications

<b>Lamp category</b>	LED	<b>Mountings</b>	Surface
<b>Power (W)</b>	8.8W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		
<b>Net lumen (lm)</b>	568		

### Optical

<b>Lighting type</b>	Indirect, Direct
<b>LED type</b>	Top LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Diffused light
<b>Beam angle (°)</b>	88
<b>Beam angle C90-270 (°)</b>	99



<b>Beam Angle: 88°</b>		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
1	253	1.94
2	63	3.88
3	28	5.82
4	16	7.76
5	10	9.70

Luminous flux luminaire  
568 lm

### Electrical

<b>Voltage (V)</b>	24.00	<b>Insulation class</b>	III
<b>Dimmable</b>	No		
<b>Driver</b>	Remote excluded		
<b>Driver type</b>	Non Dimmable		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Anodized Aluminium
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	0.096
<b>Length (mm)</b>	563

### Note

Installation cables and driver not included. To be ordered separately. Not compatible with spots. Non dimmable.



## LED Squad Mini 563 mm



---

Connection cable 150 mm  
06.0098.00



---

Electronic transformer with constant  
voltage (24V) for LED. 100/240V. 60W  
60.9089



---

Electronic transformer with constant  
voltage (24V) for LED. 100/240V. 25W  
60.8703



---

Feed cable 2500 mm  
06.0097.00