

## LED Squad Mini 563 mm. 10 Units Kit

### 03.4063.29.1Y - Anodized Aluminium



Luminary for surface installation with LED light source. Composed of an extruded aluminum profile to which LED linear modules are incorporated. Invisible dots with continuous light. It has a fast connector in order to join modules of different lengths without wiring. It has a magnetic fixing system on metal surfaces or brackets to screw on...

Luminary for surface installation with LED light source. Composed of an extruded aluminum profile to which LED linear modules are incorporated. Invisible dots with continuous light. It has a fast connector in order to join modules of different lengths without wiring. It has a magnetic fixing system on metal surfaces or brackets to screw on conventional surfaces.




### Main specifications

Lamp category	LED
Power (W)	8.8W
Net lumen (lm)	568
Mountings	Surface
Environment	Indoor


### Optical

Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	88
Beam angle C90-270 (°)	99



Beam Angle:	88°		
	h(m)	E(lx)	D(m)
1	253	1.94	
2	63	3.88	
3	28	5.82	
4	16	7.76	
5	10	9.70	

Luminous flux luminaire  
568 lm



### Electrical

Voltage (V)	24.00	Insulation class	III
Dimmable	No		
Driver	Remote		
Driver type	Electronic		
Emergency	Without		


### Physical

Color	Anodized Aluminium
Orientation	Fixed
Weight (kg)	0.96
Length (mm)	563

### Note

Installation cables and driver not included. To be ordered separately. Not compatible with spots. Non dimmable.

### Certification / Marking



## LED Squad Mini 563 mm. 10 Units Kit



---

Feed cable 2500 mm  
06.0097.00



---

Electronic transformer with constant  
voltage (24V) for LED. 100/240V. 60W  
60.9089



---

Connection cable 150 mm  
06.0098.00



---

Electronic transformer with constant  
voltage (24V) for LED. 100/240V. 25W  
60.8703