



Light Bell Dimmable Push

■ 07.9641.14ADP - Black

Suspended luminaire for mounting on the ceiling with LED light source. (4 metres maximum distance to ceiling). Power supply source integrated into luminaire housing. Reflector not included; supplied separately.

Main specifications

Number of heads	1
Lamp category	LED
Power (W)	55W
CCT (K)	2700K
CRI	90


Mountings Environment

Suspension Indoor dry location



Optical

ignting type	Direct
.ED type	LED array
ight distribution	Symmetric
Optical type	Spot
Beam angle (°)	78
Beam angle C90-270 (°)	78



79° Beam Angle: h(m) = E(Ix)D(m) 2077 1.66 2 519 3.32 3 231 4.97 4 130 6.63 5 83 8.29

Luminous flux luminaire 3099 lm (EXTREME CUT OFF)

	128
	287
ø228	412

1 03	F	I P 20	EAC	CE	RETILAP
GWT 850°					

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	35.20	Insulation class	1
Dimmable	Yes		
Driver	Integrated		

Dimmable Push

Driver type Physical

Color	Black
Orientation	Fixed
Weight (kg)	3.81

Note

Pin-block type dissipater. Please ask us for a higher IP. Includes a 4-meter suspension cable.

Light Bell Dimmable Push







Light Bell 07.9630.18



Light Bell 07.9630.76



Light Bell 07.9630.7C



Light Bell 07.9630.CE



Light Bell 07.9630.70



Light Bell 07.9630.AN



Rosette IP54 08.8775.40

Rosette for indoors. IP20. Dimmable Push/Dali F0557020

Light Bell 07.9630.AP



Rosette for indoors. IP20. Non Dimmable F0556020