



Light Bell No Dimmable

■ 07.9641.14A - Black


Suspended luminaire for mounting on the ceiling with LED light source. (4 metres maximum distance to ceiling). Power supply source integrated into luminaire housing. Reflector not included; supplied separately.

Main specifications

Number of heads	1	Mountings	Suspension
Lamp category	LED	Environment	Indoor dry location
Power (W)	55W		
CCT (K)	2700K		
CRI	90		

Optical


Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	78
Beam angle C90-270 (°)	78



Beam Angle: 79°

h(m)	E(lx)	D(m)
1	2077	1.66
2	519	3.32
3	231	4.97
4	130	6.63
5	83	8.29

Luminous flux luminaire
3099 lm (EXTREME CUT OFF)



Electrical


Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	35.20	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		

Physical

Color	Black
Orientation	Fixed
Weight (kg)	3.81

Note

Pin-block type dissipater. Please ask us for a higher IP. Includes a 4-meter suspension cable.



Light Bell No Dimmable



Light Bell
07.9630.7C



Light Bell
07.9630.CE



Light Bell
07.9630.70



Light Bell
07.9630.AN



Rosette IP54
08.8775.40



Rosette for indoors. IP20. Dimmable
Push/Dali
F0557020



Light Bell
07.9630.AP



Rosette for indoors. IP20. Non
Dimmable
F0556020



Light Bell
07.9630.18



Light Bell
07.9630.76