



Light Shadow Adjustable No Trim 12 Spots Optic Medium

03.9470.40A - White/White

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V).




Main specifications

Number of heads	1	Net lumen (lm)	2846
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	32.4W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	22
Beam angle C90-270 (°)	22



Beam Angle: 22°

h(m)	E(lx)	D(m)
1	19025	0.39
2	4756	0.78
3	2114	1.17
4	1189	1.56
5	761	1.95

Luminous flux luminaire
2846 lm (EXTREME CUT OFF)

Electrical


Frequency (Hz)	50/60	Insulation class	II
Voltage (V)	220.00		
Dimmable	No		
Driver	Remote included		
Emergency	Without		

Physical

Color	White/White	Length (mm)	429
Orientation	Adjustable		
Recessed depth (mm)	75		
Weight (kg)	0.66		
Tilt (°)	30		

Note

It requires a pre-installation frame, to be ordered separately.



Light Shadow Adjustable No Trim 12 Spots Optic Medium



Pre-installation Frame
08.0518.00

Accessory for mounting of No Trim
continuous line.
08.0059.90