





 03.7377.14A - Black/Gold

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V).



Number of heads	1	Net lumen (lm)	2597
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	32.4W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	46
Beam angle C90-270 (°)	46



h(m)	E(lx)	D(m)
1	4784	0.84
2	1196	1.69
3	532	2.53
4	299	3.38
5	191	4.22

Luminous flux luminaire
2597 lm (EXTREME CUT OFF)

Frequency (Hz)	50/60	Insulation class II
Voltage (V)	220.00	
Dimmable	No	
Driver	Remote included	
Emergency	Without	

Color	Black/Gold	Length (mm)	429
Orientation	Adjustable		
Recessed depth (mm)	75		
Weight (kg)	0.66		
Tilt (°)	30		

It requires a pre-installation frame, to be ordered separately.

Light Shadow Adjustable No Trim 12 Spots Optic Wide Flood



Accessory for mounting of No Trim
continuous line.
08.0059.90

Pre-installation Frame
08.0518.00