


Light Shadow Adjustable No Trim 2 Spots Optic Medium

■ 03.9400.14A - Black/White


Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).

**Main specifications**

| | | | |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 448 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 5.4W | Environment | Indoor dry location |
| CCT (K) | 2700K | | |
| CRI | 90 | | |

Optical

| | |
|------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Medium |
| Beam angle (°) | 22 |
| Beam angle C90-270 (°) | 22 |



Beam Angle: 22°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 2996 | 0.39 |
| 2 | 749 | 0.78 |
| 3 | 333 | 1.17 |
| 4 | 187 | 1.56 |
| 5 | 120 | 1.95 |

Luminous flux luminaire
448 lm (EXTREME CUT OFF)**Electrical**

| | | | |
|----------------|-----------------|------------------|----|
| Frequency (Hz) | 50/60 | Insulation class | II |
| Voltage (V) | 220.00 | | |
| Dimmable | No | | |
| Driver | Remote included | | |
| Emergency | Without | | |

Physical

| | | | |
|---------------------|-------------|-------------|----|
| Color | Black/White | Length (mm) | 79 |
| Orientation | Adjustable | | |
| Recessed depth (mm) | 150 | | |
| Weight (kg) | 0.25 | | |
| Tilt (°) | 30 | | |

Note

It requires a pre-installation frame, to be ordered separately.

Light Shadow Adjustable No Trim 2 Spots Optic Medium



Accessory for mounting of No Trim
continuous line.
08.0059.90

Pre-installation Frame
08.0515.00