




## Light Shadow Adjustable No Trim 2 Spots Optic Spot

03.8920.14A - Black/White

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	475
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	5.4W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	10
<b>Beam angle C90-270 (°)</b>	10



<b>Beam Angle:</b>	10°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	8680	0.17	
2	2170	0.35	
3	964	0.52	
4	542	0.70	
5	347	0.87	

Luminous flux luminaire  
475 lm (EXTREME CUT OFF)

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	II
<b>Voltage (V)</b>	220.00		
<b>Dimmable</b>	No		
<b>Driver</b>	Remote included		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Black/White	<b>Length (mm)</b>	79
<b>Orientation</b>	Adjustable		
<b>Recessed depth (mm)</b>	150		
<b>Weight (kg)</b>	0.25		
<b>Tilt (°)</b>	30		

### Note

It requires a pre-installation frame, to be ordered separately.

## Light Shadow Adjustable No Trim 2 Spots Optic Spot



---

Accessory for mounting of No Trim  
continuous line.  
08.0059.90

---

Pre-installation Frame  
08.0515.00