

Light Shadow Adjustable No Trim 4 Spots Optic Flood

03.9428.14A - Black/Gold

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included.




Main specifications

Number of heads	1	Environment	Indoor dry location
Lamp category	LED		
Power (W)	10.8W		
Net lumen (lm)	732		
Mountings	Ceiling recessed		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	33
Beam angle C90-270 (°)	33



Beam Angle:	33°		
h(m)	E(lx)	D(m)	
1	2253	0.60	
2	563	1.20	
3	250	1.79	
4	141	2.39	
5	90	2.99	

Luminous flux luminaire
732 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Insulation class	II
Voltage (V)	220.00		
Dimmable	No		
Driver	Remote included		
Emergency	Without		

Physical

Color	Black/Gold	Length (mm)	149
Orientation	Adjustable		
Recessed depth (mm)	75		
Weight (kg)	0.34		
Tilt (°)	30		

Note

It requires a pre-installation frame, to be ordered separately.



Light Shadow Adjustable No Trim 4 Spots Optic Flood



Pre-installation Frame
08.0516.00

Accessory for mounting of No Trim
continuous line.
08.0059.90