## Light Shadow Adjustable No Trim 4 Spots Optic Spot

03.8924.14A - Black/White


Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).

Main specifications Number of heads Lamp category Power (W) CCT (K) CRI	1 LED 10.8W 2700K 90	Net lumen (lm) Mountings Environment		751 Ceiling recessed Indoor dry location		
Optical Lighting type	Direct			Paa	m Angle:	10°
LED type Light distribution	Power LED Symmetric	90°	90°	h(m)		D(m)
Optical type Beam angle (°) Beam angle C90-270 (°)	Spot 10 10	60°	60°	1	, <u>1</u> 3743	0.17
		bu v		2	3436	0.35
				3	1527	0.52
				4	859	0.70
		3́0°	1 1	5	550	0.87
Electrical						
Frequency (Hz) Voltage (V) Dimmable Driver Emergency	50/60 220.00 No Remote included Without	Insulation class	II			
Physical						
Color Orientation Recessed depth (mm) Weight (kg) Tilt (°)	Black/White Adjustable 75 0.34 30	Length (mm)	149			

## Note

It requires a pre-installation frame, to be ordered separately.





<b>K</b> 03	V	<b>І</b> Р 20	EAC	CE	RETILAP
GWT 850°					

## Light Shadow Adjustable No Trim 4 Spots Optic Spot





Pre-installation Frame 08.0516.00

Accessory for mounting of No Trim continuous line. 08.0059.90