




03.8931.40A - White/Gold

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).









1/1/2	in sp	$\sim$	こつつきに	anc
IVIA	III SL		IL COLL	เมเธ
	-			•

 Number of heads
 1

 Lamp category
 LED

 Power (W)
 10.8W

 CCT (K)
 3000K

 CRI
 90


Net lumen (lm) Mountings Environment

785 Ceiling recessed

Ceiling recessed Indoor dry location

## Optical

Lighting type Direct
LED type Power LED
Light distribution Symmetric
Optical type Spot
Beam angle (°) 10
Beam angle C90-270 (°) 10



Luminous flux luminaire 785 lm (EXTREME CUT OFF)

Be	10°	
h(n	n) E( <b>l</b> x)	D(m)
1_	13891	0.18
2	3473	0.36
3	1543	0.55
4	868	0.73
5	556	0.91

## Electrical

 Frequency (Hz)
 50/60

 Voltage (V)
 220.00

 Dimmable
 No

 Driver
 Remote included

Insulation class

Emergency Physical

Color White/Gold
Orientation Adjustable
Recessed depth (mm) 75
Weight (kg) 0.34
Tilt (°) 30

Length (mm) 149

## Note

It requires a pre-installation frame, to be ordered separately.

Without

## Light Shadow Adjustable No Trim 4 Spots Optic Spot





Accessory for mounting of No Trim continuous line. 08.0059.90

Pre-installation Frame 08.0516.00