



## Light Shadow Adjustable No Trim 4 Spots Optic Wide Flood

03.7362.14A - Black/White

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).




## Main specifications

Number of heads	1	Net lumen (lm)	780
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	10.8W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

## Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	45
Beam angle C90-270 (°)	45



Beam Angle:	45°	
h(m)	E(lx)	D(m)
1	1454	0.83
2	363	1.67
3	162	2.50
4	91	3.34
5	58	4.17

Luminous flux luminaire  
780 lm (EXTREME CUT OFF)

## Electrical

Frequency (Hz)	50/60	Insulation class	II
Voltage (V)	220.00		
Dimmable	No		
Driver	Remote included		
Emergency	Without		

## Physical

<b>Color</b>	Black/White	<b>Length (mm)</b>	149
<b>Orientation</b>	Adjustable		
<b>Recessed depth (mm)</b>	75		
<b>Weight (kg)</b>	0.34		
<b>Tilt (°)</b>	30		

### Note

It requires a pre-installation frame, to be ordered separately.

Light Shadow Adjustable No Trim 4 Spots Optic Wide Flood



---

Accessory for mounting of No Trim  
continuous line.  
08.0059.90

---

Pre-installation Frame  
08.0516.00