


03.9443.40A - White/Gold


Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).











Number of heads LED Lamp category Power (W) 21.6W CCT (K) 2700K CRI 90


Net lumen (lm) Mountings Environment

1781 Ceiling recessed

Indoor dry location

Optical

Lighting type Direct LED type Power LED Light distribution Symmetric Optical type Medium Beam angle (°) 22 Beam angle C90-270 (°) 22



11982 0.39 2 2995 0.77 3 1331 1.16 4 749 1.55 5 479 1.94

Beam Angle:

h(m)

E(lx)

22°

D(m)

Luminous flux luminaire 1781 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz) 50/60 Voltage (V) 220.00 Dimmable No Driver

Remote included **Emergency** Without

Physical

White/Gold Orientation Adjustable Recessed depth (mm) 75 Weight (kg) 0.50 Tilt (°) 30

Insulation class

Length (mm) 289

Note

It requires a pre-installation frame, to be ordered separately.

Light Shadow Adjustable No Trim 8 Spots Optic Medium





Accessory for mounting of No Trim continuous line. 08.0059.90

Pre-installation Frame 08.0517.00