


## Light Shadow Adjustable No Trim 8 Spots Optic Medium

■ □ 03.9450.14A - Black/White

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1878
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	21.6W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	22
<b>Beam angle C90-270 (°)</b>	22



Beam Angle: 22°

	h(m)	E(lx)	D(m)
1	12556	0.39	
2	3139	0.78	
3	1395	1.17	
4	785	1.56	
5	502	1.95	


Luminous flux luminaire  
1878 lm (EXTREME CUT OFF)

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	II
<b>Voltage (V)</b>	220.00		
<b>Dimmable</b>	No		
<b>Driver</b>	Remote included		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Black/White	<b>Length (mm)</b>	289
<b>Orientation</b>	Adjustable		
<b>Recessed depth (mm)</b>	75		
<b>Weight (kg)</b>	0.50		
<b>Tilt (°)</b>	30		



### Note

It requires a pre-installation frame, to be ordered separately.

## Light Shadow Adjustable No Trim 8 Spots Optic Medium



---

Pre-installation Frame  
08.0517.00

---

Accessory for mounting of No Trim  
continuous line.  
08.0059.90