


## Light Shadow Adjustable No Trim 8 Spots Optic Medium

03.9453.40A - White/Gold

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

|                        |       |                       |                     |
|------------------------|-------|-----------------------|---------------------|
| <b>Number of heads</b> | 1     | <b>Net lumen (lm)</b> | 1866                |
| <b>Lamp category</b>   | LED   | <b>Mountings</b>      | Ceiling recessed    |
| <b>Power (W)</b>       | 21.6W | <b>Environment</b>    | Indoor dry location |
| <b>CCT (K)</b>         | 3000K |                       |                     |
| <b>CRI</b>             | 90    |                       |                     |

### Optical

|                               |           |
|-------------------------------|-----------|
| <b>Lighting type</b>          | Direct    |
| <b>LED type</b>               | Power LED |
| <b>Light distribution</b>     | Symmetric |
| <b>Optical type</b>           | Medium    |
| <b>Beam angle (°)</b>         | 22        |
| <b>Beam angle C90-270 (°)</b> | 22        |



|                    |              |             |  |
|--------------------|--------------|-------------|--|
| <b>Beam Angle:</b> | 22°          |             |  |
| <b>h(m)</b>        | <b>E(lx)</b> | <b>D(m)</b> |  |
| 1                  | 12472        | 0.39        |  |
| 2                  | 3118         | 0.78        |  |
| 3                  | 1386         | 1.17        |  |
| 4                  | 779          | 1.56        |  |
| 5                  | 499          | 1.95        |  |

Luminous flux luminaire  
1866 lm (EXTREME CUT OFF)

### Electrical


|                       |                 |                         |    |
|-----------------------|-----------------|-------------------------|----|
| <b>Frequency (Hz)</b> | 50/60           | <b>Insulation class</b> | II |
| <b>Voltage (V)</b>    | 220.00          |                         |    |
| <b>Dimmable</b>       | No              |                         |    |
| <b>Driver</b>         | Remote included |                         |    |
| <b>Emergency</b>      | Without         |                         |    |

### Physical

|                            |            |                    |     |
|----------------------------|------------|--------------------|-----|
| <b>Color</b>               | White/Gold | <b>Length (mm)</b> | 289 |
| <b>Orientation</b>         | Adjustable |                    |     |
| <b>Recessed depth (mm)</b> | 75         |                    |     |
| <b>Weight (kg)</b>         | 0.50       |                    |     |
| <b>Tilt (°)</b>            | 30         |                    |     |

### Note

It requires a pre-installation frame, to be ordered separately.



## Light Shadow Adjustable No Trim 8 Spots Optic Medium



---

Accessory for mounting of No Trim  
continuous line.  
08.0059.90

---

Pre-installation Frame  
08.0517.00