




03.8933.14A - Black/Black

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).











21.6W CCT (K) 2700K CRI 90

Net lumen (lm) Mountings Environment

1747 Ceiling recessed Indoor dry location

Optical

Lighting type Direct LED type Power LED Light distribution Symmetric Optical type Spot Beam angle (°) 10 Beam angle C90-270 (°) 10

	1000
90°	90°
600	
60°	606
K XII	LX X
$ \times \setminus $	
\times	
30° \ 3153	3 cd √ 30°

Luminous flux luminaire

Beam Angle: 10° h(m) = E(Ix)D(m) 31533 0.18 7883 0.36 3 3504 0.54 1971 0.72

1261

0.90

1747 lm (EXTREME CUT OFF)

E	lect	ric	al

50/60 Frequency (Hz) Voltage (V) 220.00 Dimmable No

Driver Remote included **Emergency** Without

Physical

Color Black/Black Orientation Adjustable Recessed depth (mm) 75 Weight (kg) 0.50 Tilt (°) 30

Insulation class

Length (mm)

289

Note

It requires a pre-installation frame, to be ordered separately.

Light Shadow Adjustable No Trim 8 Spots Optic Spot





Accessory for mounting of No Trim continuous line. 08.0059.90

Pre-installation Frame 08.0517.00