




03.8934.14A - Black/Chrome

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).









•	
Number of heads	1
Lamp category	LED
Power (W)	21.6W
CCT (K)	2700K
CRI	90

Main specifications

Net lumen (lm) Mountings Environment

1819 Ceiling recessed Indoor dry location

Beam Angle:

h(m) = E(Ix)

3

32048

8012

3561

10°

D(m)

0.18

0.36


0.55

0.73

0.91

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	10
Beam angle C90-270 (°)	10



1819 lm (EXTREME CUT OFF)

Insulation class

Length (mm)

2003 1282 Luminous flux luminaire

289

Electrical

Frequency (Hz)	50/60
Voltage (V)	220.00
Dimmable	No
Deiror	Domost

Driver Remote included **Emergency** Without

Physical

Color	Black/Chrome
Orientation	Adjustable
Recessed depth (mm)	75
Weight (kg)	0.50
Tilt (°)	30

Note

It requires a pre-installation frame, to be ordered separately.

Light Shadow Adjustable No Trim 8 Spots Optic Spot





Accessory for mounting of No Trim continuous line. 08.0059.90

Pre-installation Frame 08.0517.00