

## Light Shadow Adjustable No Trim 8 Spots Optic Spot

03.8937.40A - White/Black

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

|                        |       |                       |                     |
|------------------------|-------|-----------------------|---------------------|
| <b>Number of heads</b> | 1     | <b>Net lumen (lm)</b> | 1830                |
| <b>Lamp category</b>   | LED   | <b>Mountings</b>      | Ceiling recessed    |
| <b>Power (W)</b>       | 21.6W | <b>Environment</b>    | Indoor dry location |
| <b>CCT (K)</b>         | 3000K |                       |                     |
| <b>CRI</b>             | 90    |                       |                     |

### Optical

|                               |           |
|-------------------------------|-----------|
| <b>Lighting type</b>          | Direct    |
| <b>LED type</b>               | Power LED |
| <b>Light distribution</b>     | Symmetric |
| <b>Optical type</b>           | Spot      |
| <b>Beam angle (°)</b>         | 10        |
| <b>Beam angle C90-270 (°)</b> | 10        |



|                    |              |             |  |
|--------------------|--------------|-------------|--|
| <b>Beam Angle:</b> | 10°          |             |  |
| <b>h(m)</b>        | <b>E(lx)</b> | <b>D(m)</b> |  |
| 1                  | 33034        | 0.18        |  |
| 2                  | 8259         | 0.36        |  |
| 3                  | 3670         | 0.54        |  |
| 4                  | 2065         | 0.72        |  |
| 5                  | 1321         | 0.90        |  |

Luminous flux luminaire  
1830 lm (EXTREME CUT OFF)

### Electrical


|                       |                 |                         |    |
|-----------------------|-----------------|-------------------------|----|
| <b>Frequency (Hz)</b> | 50/60           | <b>Insulation class</b> | II |
| <b>Voltage (V)</b>    | 220.00          |                         |    |
| <b>Dimmable</b>       | No              |                         |    |
| <b>Driver</b>         | Remote included |                         |    |
| <b>Emergency</b>      | Without         |                         |    |

### Physical

|                            |             |                    |     |
|----------------------------|-------------|--------------------|-----|
| <b>Color</b>               | White/Black | <b>Length (mm)</b> | 289 |
| <b>Orientation</b>         | Adjustable  |                    |     |
| <b>Recessed depth (mm)</b> | 75          |                    |     |
| <b>Weight (kg)</b>         | 0.50        |                    |     |
| <b>Tilt (°)</b>            | 30          |                    |     |

### Note

It requires a pre-installation frame, to be ordered separately.



## Light Shadow Adjustable No Trim 8 Spots Optic Spot



---

Accessory for mounting of No Trim  
continuous line.  
08.0059.90

---

Pre-installation Frame  
08.0517.00