



## Light Shadow Adjustable No Trim 8 Spots Optic Wide Flood

03.7369.14A - Black/Gold

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1727
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	21.6W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	2700K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Wide flood
<b>Beam angle (°)</b>	46
<b>Beam angle C90-270 (°)</b>	46



<b>Beam Angle:</b>	46°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	3181	0.84	
2	795	1.69	
3	353	2.53	
4	199	3.38	
5	127	4.22	


Luminous flux luminaire  
1727 lm (EXTREME CUT OFF)

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	II
<b>Voltage (V)</b>	220.00		
<b>Dimmable</b>	No		
<b>Driver</b>	Remote included		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Black/Gold	<b>Length (mm)</b>	289
<b>Orientation</b>	Adjustable		
<b>Recessed depth (mm)</b>	75		
<b>Weight (kg)</b>	0.50		
<b>Tilt (°)</b>	30		



### Note

It requires a pre-installation frame, to be ordered separately.

## Light Shadow Adjustable No Trim 8 Spots Optic Wide Flood



---

Pre-installation Frame  
08.0517.00

---

Accessory for mounting of No Trim  
continuous line.  
08.0059.90