


Light Shadow Adjustable No Trim Dali Version 2 Spots Optic Flood

03.9415.40ADA - White/White

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).




Main specifications

| | | | |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 468 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 5.4W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 90 | | |

Optical

| | |
|------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Flood |
| Beam angle (°) | 33 |
| Beam angle C90-270 (°) | 33 |



Beam Angle: 33°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 1459 | 0.59 |
| 2 | 365 | 1.18 |
| 3 | 162 | 1.78 |
| 4 | 91 | 2.37 |
| 5 | 58 | 2.96 |

Luminous flux luminaire
468 lm (EXTREME CUT OFF)

Electrical

| | | | |
|----------------|-----------------|------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 220.00 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Remote included | | |
| Driver type | Dimmable DALI | | |
| | 1 | | |

Physical

| | | | |
|---------------------|-------------|-------------|----|
| Color | White/White | Length (mm) | 79 |
| Orientation | Adjustable | | |
| Recessed depth (mm) | 150 | | |
| Weight (kg) | 0.25 | | |
| Tilt (°) | 30 | | |

Note

It requires a pre-installation frame, to be ordered separately.



Light Shadow Adjustable No Trim Dali Version 2 Spots Optic Flood



Pre-installation Frame
08.0515.00

Accessory for mounting of No Trim
continuous line.
08.0059.90