


## Light Shadow Adjustable No Trim Dali Version 2 Spots Optic Flood

03.9415.40ADA - White/White

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	468
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	5.4W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Flood
<b>Beam angle (°)</b>	33
<b>Beam angle C90-270 (°)</b>	33



Beam Angle:	33°		
	h(m)	E(lx)	D(m)
	1	1459	0.59
	2	365	1.18
	3	162	1.78
	4	91	2.37
	5	58	2.96

Luminous flux luminaire  
468 lm (EXTREME CUT OFF)

### Electrical


<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote included		
<b>Driver type</b>	Dimmable DALI		
	1		

### Physical

<b>Color</b>	White/White	<b>Length (mm)</b>	79
<b>Orientation</b>	Adjustable		
<b>Recessed depth (mm)</b>	150		
<b>Weight (kg)</b>	0.25		
<b>Tilt (°)</b>	30		

### Note

It requires a pre-installation frame, to be ordered separately.



# Light Shadow Adjustable No Trim Dali Version 2 Spots Optic Flood



---

Pre-installation Frame  
08.0515.00

---

Accessory for mounting of No Trim  
continuous line.  
08.0059.90