

Light Shadow Adjustable No Trim Dali Version 4 Spots Optic Flood

03.9437.14ADA - Black/Chrome

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).




Main specifications

| | | | |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 803 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 10.8W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 90 | | |

Optical

| | |
|------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Flood |
| Beam angle (°) | 33 |
| Beam angle C90-270 (°) | 33 |



| | | | |
|-------------|------|-------|------|
| Beam Angle: | 33° | | |
| | h(m) | E(lx) | D(m) |
| 1 | 2485 | 0.60 | |
| 2 | 621 | 1.19 | |
| 3 | 276 | 1.79 | |
| 4 | 155 | 2.38 | |
| 5 | 99 | 2.98 | |

Luminous flux luminaire
803 lm (EXTREME CUT OFF)

Electrical


| | | | |
|----------------|-----------------|------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 220.00 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Remote included | | |
| Driver type | Dimmable DALI | | |
| | 1 | | |

Physical

| | | | |
|---------------------|--------------|-------------|-----|
| Color | Black/Chrome | Length (mm) | 149 |
| Orientation | Adjustable | | |
| Recessed depth (mm) | 75 | | |
| Weight (kg) | 0.34 | | |
| Tilt (°) | 30 | | |

Note

It requires a pre-installation frame, to be ordered separately.



Light Shadow Adjustable No Trim Dali Version 4 Spots Optic Flood



Pre-installation Frame
08.0516.00

Accessory for mounting of No Trim
continuous line.
08.0059.90