


03.9423.40ADA - White/Gold

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).

Number of heads	1	Net lumen (lm)	738
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	10.8W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	22
Beam angle C90-270 (°)	22


$$h(m) \quad E(x) \quad D(m)$$

1	4937	0.39
2	1234	0.78
3	549	1.17
4	309	1.56
5	197	1.95

Luminous flux luminaire
738 lm (EXTREME CUT OFF)

Frequency (Hz)	50/60	Emergency Insulation class	Without II
Voltage (V)	220.00		
Dimmable	Yes		
Driver	Remote included		
Driver type	Dimmable DALI 1		

Color	White/Gold	Length (mm)	149
Orientation	Adjustable		
Recessed depth (mm)	75		
Weight (kg)	0.34		
Tilt (°)	30		

It requires a pre-installation frame, to be ordered separately.

Light Shadow Adjustable No Trim Dali Version 4 Spots Optic Medium



Pre-installation Frame
08.0516.00

Accessory for mounting of No Trim
continuous line.
08.0059.90