

Light Shadow Adjustable No Trim Dali Version 4 Spots Optic Medium

03.9433.14ADA - Black/Gold


Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).

Main specifications

Number of heads	1	Net lumen (lm)	788
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	10.8W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	22
Beam angle C90-270 (°)	22



Beam Angle:	22°	
h(m)	E(lx)	D(m)
1	5266	0.39
2	1316	0.78
3	585	1.17
4	329	1.56
5	211	1.95

Luminous flux lumineuse
788 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency Insulation class	Without II
Voltage (V)	220.00		
Dimmable	Yes		
Driver	Remote included		
Driver type	Dimmable DALI		
	1		

Physical

Color	Black/Gold	Length (mm)	149
Orientation	Adjustable		
Recessed depth (mm)	75		
Weight (kg)	0.34		
Tilt (°)	30		

Note

It requires a pre-installation frame, to be ordered separately.

Light Shadow Adjustable No Trim Dali Version 4 Spots Optic Medium



Accessory for mounting of No Trim
continuous line.
08.0059.90

Pre-installation Frame
08.0516.00