


## Light Shadow Adjustable No Trim Dali Version 4 Spots Optic Wide Flood

03.7358.40ADA - White/White

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 731                 |
| Lamp category   | LED   | Mountings      | Ceiling recessed    |
| Power (W)       | 10.8W | Environment    | Indoor dry location |
| CCT (K)         | 2700K |                |                     |
| CRI             | 90    |                |                     |

### Optical

|                        |            |
|------------------------|------------|
| Lighting type          | Direct     |
| LED type               | Power LED  |
| Light distribution     | Symmetric  |
| Optical type           | Wide flood |
| Beam angle (°)         | 45         |
| Beam angle C90-270 (°) | 45         |



Beam Angle: 45°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 1363  | 0.83 |
| 2    | 341   | 1.67 |
| 3    | 151   | 2.50 |
| 4    | 85    | 3.34 |
| 5    | 55    | 4.17 |

Luminous flux luminaire  
731 lm (EXTREME CUT OFF)

### Electrical


|                |                 |                  |         |
|----------------|-----------------|------------------|---------|
| Frequency (Hz) | 50/60           | Emergency        | Without |
| Voltage (V)    | 220.00          | Insulation class | II      |
| Dimmable       | Yes             |                  |         |
| Driver         | Remote included |                  |         |
| Driver type    | Dimmable DALI   |                  |         |
|                | 1               |                  |         |

### Physical

|                     |             |             |     |
|---------------------|-------------|-------------|-----|
| Color               | White/White | Length (mm) | 149 |
| Orientation         | Adjustable  |             |     |
| Recessed depth (mm) | 75          |             |     |
| Weight (kg)         | 0.34        |             |     |
| Tilt (°)            | 30          |             |     |

### Note

It requires a pre-installation frame, to be ordered separately.



# Light Shadow Adjustable No Trim Dali Version 4 Spots Optic Wide Flood



---

Pre-installation Frame  
08.0516.00

---

Accessory for mounting of No Trim  
continuous line.  
08.0059.90