






Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).












Number of heads	1	Net lumen (lm)	1813
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	21.6W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

## Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	22
Beam angle C90-270 (°)	22



JΟ		121	<b>43</b> (	ca t	30 (
Lum	ino	us	flux	lumi	inaire
1813	lm	(FX	TREN	ΛΕ CU	T OFF)

Without

Beam Angle:		22°
h(n	n) E( <b>l</b> x)	D(m)
1_	12123	0.39
2	3031	0.78
3	1347	1.17
4	758	1.56
5	485	1.95

#### **Electrical**

Frequency (Hz)	50/60	Emergency
Voltage (V)	220.00	Insulation class
Dimmable	Yes	
Driver	Remote included	
Driver type	Dimmable DALI	

## Physical

Color	White/Chrome	Length (mm)	289
Orientation	Adjustable		
Recessed depth (mm)	75		
Weight (kg)	0.50		
Tilt (°)	30		

#### Note

It requires a pre-installation frame, to be ordered separately.

# Light Shadow Adjustable No Trim Dali Version 8 Spots Optic Medium





Pre-installation Frame 08.0517.00

Accessory for mounting of No Trim continuous line. 08.0059.90