





03.9443.14ADA - Black/Gold

90

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).




Number of heads	1	Net lumen (lm)	1/81
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	21.6W	Environment	Indoor dry location
CCT (K)	2700K		

### Optical

CRI

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	22
Beam angle C90-270 (°)	22




Luminous flux luminaire 1781 lm (EXTREME CUT OFF)

Without

Beam Angle:		22°
h(n	n) E(lx)	D(m)
1_	11982	0.39
2	2995	0.77
3	1331	1.16
4	749	1.55
5	479	1.94











Electrical	
Frequency (Hz)	50/60
Voltage (V)	220.00
Dimmable	Yes
Driver	Remote included
Driver type	Dimmable DALI

**Emergency** Insulation class

## Physical

Color	Black/Gold	Length (mm)	289
Orientation	Adjustable		
Recessed depth (mm)	75		
Weight (kg)	0.50		
Tilt (°)	30		

#### Note

It requires a pre-installation frame, to be ordered separately.

# Light Shadow Adjustable No Trim Dali Version 8 Spots Optic Medium





Accessory for mounting of No Trim continuous line. 08.0059.90

Pre-installation Frame 08.0517.00