75x303

 $\overline{2}5$

20 EAL CE RETILAP

K || \[

GWT 850°

Light Shadow Adjustable No Trim Dali Version 8 Spots Optic Spot

03.8938.40ADA - White/Chrome

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).

Main specifications Number of heads Lamp category Power (W) CCT (K) CRI	1 LED 21.6W 3000K 90	Net lumen (lm) Mountings Environment	1906 Ceiling recessed Indoor dry location	
Optical Lighting type LED type Light distribution Optical type Beam angle (°) Beam angle C90-270 (°)	Direct Power LED Symmetric Spot 10 10	90° 60° 30° 33574 c Luminous flux I 1906 lm (EXTREM	uminaire	Beam Angle: 10° h(m) E(lx) D(m) 1 33574 0.18 2 8394 0.36 3 3730 0.55 4 2098 0.73 5 1343 0.91
Electrical Frequency (Hz) Voltage (V) Dimmable Driver Driver type	50/60 220.00 Yes Remote included Dimmable DALI 1	Emergency Insulation class	Without II	
Physical Color Orientation Recessed depth (mm) Weight (kg) Tilt (°)	White/Chrome Adjustable 75 0.50 30	Length (mm)	289	

Note

It requires a pre-installation frame, to be ordered separately.

Light Shadow Adjustable No Trim Dali Version 8 Spots Optic Spot





Pre-installation Frame 08.0517.00

Accessory for mounting of No Trim continuous line. 08.0059.90