

Light Shadow Adjustable No Trim Dali Version 8 Spots Optic Wide Flood

■ 03.7367.40ADA - White/Black

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 1773 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 21.6W | Environment | Indoor dry location |
| CCT (K) | 2700K | | |
| CRI | 90 | | |


Optical

| | |
|-------------------------------|------------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Wide flood |
| Beam angle (°) | 46 |
| Beam angle C90-270 (°) | 46 |



| | | | |
|--------------------|-------------|--------------|-------------|
| Beam Angle: | 46° | | |
| | h(m) | E(lx) | D(m) |
| | 1 | 3363 | 0.84 |
| | 2 | 841 | 1.69 |
| | 3 | 374 | 2.53 |
| | 4 | 210 | 3.38 |
| | 5 | 135 | 4.22 |

Luminous flux luminaire
1773 lm (EXTREME CUT OFF)



Electrical


| | | | |
|-----------------------|-----------------|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 220.00 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Remote included | | |
| Driver type | Dimmable DALI | | |
| | 1 | | |

Physical

| | | | |
|----------------------------|-------------|--------------------|-----|
| Color | White/Black | Length (mm) | 289 |
| Orientation | Adjustable | | |
| Recessed depth (mm) | 75 | | |
| Weight (kg) | 0.50 | | |
| Tilt (°) | 30 | | |

Note

It requires a pre-installation frame, to be ordered separately.



Light Shadow Adjustable No Trim Dali Version 8 Spots Optic Wide Flood



Accessory for mounting of No Trim
continuous line.
08.0059.90

Pre-installation Frame
08.0517.00