


## Light Shadow Adjustable Trim 12 Spots Optic Spot

03.8912.14A - Black/White

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	2876
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	32.4W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	10
<b>Beam angle C90-270 (°)</b>	10



Beam Angle: 10°

h(m)	E(lx)	D(m)
1	52606	0.17
2	13152	0.35
3	5845	0.52
4	3288	0.70
5	2104	0.87

Luminous flux luminaire  
2876 lm (EXTREME CUT OFF)

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	II
<b>Voltage (V)</b>	220.00		
<b>Dimmable</b>	No		
<b>Driver</b>	Remote included		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Black/White	<b>Tilt (°)</b>	30
<b>Orientation</b>	Adjustable	<b>Length (mm)</b>	436
<b>Trim</b>	yes		
<b>Recessed depth (mm)</b>	75		
<b>Weight (kg)</b>	0.66		

### Note

Pre-Installation frame not required.

