

## Light Shadow Adjustable Trim 12 Spots Optic Wide Flood

■ 03.7325.40A - White/Black

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	2666
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	32.4W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	2700K		
<b>CRI</b>	90		


### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Wide flood
<b>Beam angle (°)</b>	46
<b>Beam angle C90-270 (°)</b>	46



<b>Beam Angle: 46°</b>		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
1	5058	0.84
2	1264	1.69
3	562	2.53
4	316	3.38
5	202	4.22

Luminous flux luminaire  
2666 lm (EXTREME CUT OFF)




### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	II
<b>Dimmable</b>	No		
<b>Driver</b>	Remote		
<b>Driver type</b>	Electronic		

### Physical

<b>Color</b>	White/Black	<b>Tilt (°)</b>	30
<b>Orientation</b>	Adjustable	<b>Length (mm)</b>	436
<b>Trim</b>	yes		
<b>Recessed depth (mm)</b>	75		
<b>Weight (kg)</b>	0.66		



### Note

Pre-Installation frame not required.