


## Light Shadow Adjustable Trim 2 Spots Optic Wide Flood

03.7303.40A - White/Gold

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 432                 |
| Lamp category   | LED   | Mountings      | Ceiling recessed    |
| Power (W)       | 5.4W  | Environment    | Indoor dry location |
| CCT (K)         | 2700K |                |                     |
| CRI             | 90    |                |                     |

### Optical

|                        |            |
|------------------------|------------|
| Lighting type          | Direct     |
| LED type               | Power LED  |
| Light distribution     | Symmetric  |
| Optical type           | Wide flood |
| Beam angle (°)         | 46         |
| Beam angle C90-270 (°) | 46         |



|             |       |      |
|-------------|-------|------|
| Beam Angle: |       | 46°  |
| h(m)        | E(lx) | D(m) |
| 1           | 795   | 0.84 |
| 2           | 199   | 1.69 |
| 3           | 88    | 2.53 |
| 4           | 50    | 3.38 |
| 5           | 32    | 4.22 |

Luminous flux luminaire  
432 lm (EXTREME CUT OFF)

### Electrical

|                |                 |                  |    |
|----------------|-----------------|------------------|----|
| Frequency (Hz) | 50/60           | Insulation class | II |
| Voltage (V)    | 220.00          |                  |    |
| Dimmable       | No              |                  |    |
| Driver         | Remote included |                  |    |
| Emergency      | Without         |                  |    |

### Physical

|                     |            |             |    |
|---------------------|------------|-------------|----|
| Color               | White/Gold | Tilt (°)    | 30 |
| Orientation         | Adjustable | Length (mm) | 86 |
| Trim                | yes        |             |    |
| Recessed depth (mm) | 150        |             |    |
| Weight (kg)         | 0.25       |             |    |

### Note

Pre-Installation frame not required.

