


Light Shadow Adjustable Trim 4 Spots Optic Medium

03.9322.40A - White/Chrome

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 752 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 10.8W | Environment | Indoor dry location |
| CCT (K) | 2700K | | |
| CRI | 90 | | |

Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Medium |
| Beam angle (°) | 22 |
| Beam angle C90-270 (°) | 22 |



| | | | |
|--------------------|--------------|-------------|--|
| Beam Angle: | 22° | | |
| h(m) | E(lx) | D(m) | |
| 1 | 5060 | 0.39 | |
| 2 | 1265 | 0.77 | |
| 3 | 562 | 1.16 | |
| 4 | 316 | 1.55 | |
| 5 | 202 | 1.94 | |

Luminous flux luminaire
752 lm (EXTREME CUT OFF)

Electrical

| | | | |
|-----------------------|-----------------|-------------------------|----|
| Frequency (Hz) | 50/60 | Insulation class | II |
| Voltage (V) | 220.00 | | |
| Dimmable | No | | |
| Driver | Remote included | | |
| Emergency | Without | | |

Physical

| | | | |
|----------------------------|--------------|--------------------|-----|
| Color | White/Chrome | Tilt (°) | 30 |
| Orientation | Adjustable | Length (mm) | 156 |
| Trim | yes | | |
| Recessed depth (mm) | 75 | | |
| Weight (kg) | 0.34 | | |

Note

Pre-Installation frame not required.

