



### Light Shadow Adjustable Trim 8 Spots Optic Medium

03.9342.14A - Black/Chrome

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).




#### Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 1813                |
| Lamp category   | LED   | Mountings      | Ceiling recessed    |
| Power (W)       | 21.6W | Environment    | Indoor dry location |
| CCT (K)         | 2700K |                |                     |
| CRI             | 90    |                |                     |

#### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | Power LED |
| Light distribution     | Symmetric |
| Optical type           | Medium    |
| Beam angle (°)         | 22        |
| Beam angle C90-270 (°) | 22        |



Beam Angle: 22°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 12201 | 0.39 |
| 2    | 3050  | 0.77 |
| 3    | 1356  | 1.16 |
| 4    | 763   | 1.55 |
| 5    | 488   | 1.94 |

Luminous flux luminaire  
1813 lm (EXTREME CUT OFF)

#### Electrical

|                |                 |                  |    |
|----------------|-----------------|------------------|----|
| Frequency (Hz) | 50/60           | Insulation class | II |
| Voltage (V)    | 220.00          |                  |    |
| Dimmable       | No              |                  |    |
| Driver         | Remote included |                  |    |
| Emergency      | Without         |                  |    |

#### Physical

|                     |              |             |     |
|---------------------|--------------|-------------|-----|
| Color               | Black/Chrome | Tilt (°)    | 30  |
| Orientation         | Adjustable   | Length (mm) | 296 |
| Trim                | yes          |             |     |
| Recessed depth (mm) | 75           |             |     |
| Weight (kg)         | 0.50         |             |     |

#### Note

Pre-Installation frame not required.

