

## Light Shadow Adjustable Trim 8 Spots Optic Spot

03.8906.40A - White/Chrome

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

|                        |       |                       |                     |
|------------------------|-------|-----------------------|---------------------|
| <b>Number of heads</b> | 1     | <b>Net lumen (lm)</b> | 1906                |
| <b>Lamp category</b>   | LED   | <b>Mountings</b>      | Ceiling recessed    |
| <b>Power (W)</b>       | 21.6W | <b>Environment</b>    | Indoor dry location |
| <b>CCT (K)</b>         | 3000K |                       |                     |
| <b>CRI</b>             | 90    |                       |                     |


### Optical

|                               |           |
|-------------------------------|-----------|
| <b>Lighting type</b>          | Direct    |
| <b>LED type</b>               | Power LED |
| <b>Light distribution</b>     | Symmetric |
| <b>Optical type</b>           | Spot      |
| <b>Beam angle (°)</b>         | 10        |
| <b>Beam angle C90-270 (°)</b> | 10        |



|                    |             |              |             |
|--------------------|-------------|--------------|-------------|
| <b>Beam Angle:</b> | 10°         |              |             |
|                    | <b>h(m)</b> | <b>E(lx)</b> | <b>D(m)</b> |
|                    | 1           | 33574        | 0.18        |
|                    | 2           | 8394         | 0.36        |
|                    | 3           | 3730         | 0.55        |
|                    | 4           | 2098         | 0.73        |
|                    | 5           | 1343         | 0.91        |

Luminous flux luminaire  
1906 lm (EXTREME CUT OFF)




### Electrical

|                       |                 |                         |    |
|-----------------------|-----------------|-------------------------|----|
| <b>Frequency (Hz)</b> | 50/60           | <b>Insulation class</b> | II |
| <b>Voltage (V)</b>    | 220.00          |                         |    |
| <b>Dimmable</b>       | No              |                         |    |
| <b>Driver</b>         | Remote included |                         |    |
| <b>Emergency</b>      | Without         |                         |    |

### Physical

|                            |              |                    |     |
|----------------------------|--------------|--------------------|-----|
| <b>Color</b>               | White/Chrome | <b>Tilt (°)</b>    | 30  |
| <b>Orientation</b>         | Adjustable   | <b>Length (mm)</b> | 296 |
| <b>Trim</b>                | yes          |                    |     |
| <b>Recessed depth (mm)</b> | 75           |                    |     |
| <b>Weight (kg)</b>         | 0.50         |                    |     |



### Note

Pre-Installation frame not required.