



## Light Shadow Adjustable Trim 8 Spots Optic Wide Flood

■ 03.7317.40A - White/Black

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 1773                |
| Lamp category   | LED   | Mountings      | Ceiling recessed    |
| Power (W)       | 21.6W | Environment    | Indoor dry location |
| CCT (K)         | 2700K |                |                     |
| CRI             | 90    |                |                     |

### Optical

|                        |            |
|------------------------|------------|
| Lighting type          | Direct     |
| LED type               | Power LED  |
| Light distribution     | Symmetric  |
| Optical type           | Wide flood |
| Beam angle (°)         | 46         |
| Beam angle C90-270 (°) | 46         |



Beam Angle: 46°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 3363  | 0.84 |
| 2    | 841   | 1.69 |
| 3    | 374   | 2.53 |
| 4    | 210   | 3.38 |
| 5    | 135   | 4.22 |

Luminous flux luminaire  
1773 lm (EXTREME CUT OFF)

### Electrical

|                |                 |                  |    |
|----------------|-----------------|------------------|----|
| Frequency (Hz) | 50/60           | Insulation class | II |
| Voltage (V)    | 220.00          |                  |    |
| Dimmable       | No              |                  |    |
| Driver         | Remote included |                  |    |
| Emergency      | Without         |                  |    |

### Physical

|                     |             |             |     |
|---------------------|-------------|-------------|-----|
| Color               | White/Black | Tilt (°)    | 30  |
| Orientation         | Adjustable  | Length (mm) | 296 |
| Trim                | yes         |             |     |
| Recessed depth (mm) | 75          |             |     |
| Weight (kg)         | 0.50        |             |     |

### Note

Pre-Installation frame not required.