


Light Shadow Adjustable Trim Dali Version 12 Spots Optic Medium

■ □ 03.9360.14ADA - Black/White

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V).




Main specifications

Number of heads	1	Net lumen (lm)	2696
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	32.4W	Environment	Indoor
CCT (K)	2700K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	22
Beam angle C90-270 (°)	22




Beam Angle:	22°		
	h(m)	E(lx)	D(m)
1	18024	0.39	
2	4506	0.78	
3	2003	1.17	
4	1126	1.56	
5	721	1.95	

Luminous flux luminaire
2696 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic dimmable push, Electronic dimmable DALI		

Certification / Marking



Physical

Color	Black/White	Tilt (°)	30
Orientation	Adjustable	Length (mm)	436
Trim	yes		
Recessed depth (mm)	75		
Weight (kg)	0.66		

Note

Pre-Installation frame not required.