






Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V).












Number of heads	1	Net lumen (lm)	2698
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	32.4W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	22
Beam angle C90-270 (°)	22



,00		1 10	CU	
Lumin	ous	flux	k lur	ninaire
2698 In	n (EX	(TRE	ME C	CUT OFF)

Without

В	eam Angle:	22°
h	(m) E(l x)	D(m)
1	18443	0.39
2	4611	0.78
3	2049	1.17
4	1153	1.56
5	738	1 95

Electrical

Frequency (Hz)	50/60	Emergency
Voltage (V)	220.00	Insulation class
Dimmable	Yes	
Driver	Remote included	
Driver type	Dimmable DALI	

Physical

-			
Color	Black/Black	Tilt (°)	30
Orientation	Adjustable	Length (mm)	436
Trim	yes		
Recessed depth (mm)	75		
Weight (kg)	0.66		
• •			

Note

Pre-Installation frame not required.