






Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V).












Number of heads	1	Net lumen (lm)	2736
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	32.4W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

## Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	10
Beam angle C90-270 (°)	10



,00	, 1017	, – ,	cu ,	
Lumin	ous fl	ux	lur	ninaire
2736 ln	n (EXT	REN	ME C	CUT OFF)

Without

Bea	e: 1	0	
h(m	) E(l×	:) D(	m
1	48193	3 0.	18
2	12048	3 0.3	36
3	5355	5 0.5	55
4	3012	2 0.7	73
5	1928	3 0 9	71

## **Electrical**

Frequency (Hz)	50/60	Emergency
Voltage (V)	220.00	Insulation class
Dimmable	Yes	
Driver	Remote included	
Driver type	Dimmable DALI	

## Physical

Color Orientation	White/Chrome Adjustable	Tilt (°) Length (mm)	30 436
Trim	yes		
Recessed depth (mm)	75		
Weight (kg)	0.66		

## Note

Pre-Installation frame not required.