






Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V).



 Number of heads
 1
 Net lumen (Im)
 2888

 Lamp category
 LED
 Mountings
 Ceiling recessed


 Power (W)
 32.4W
 Environment
 Indoor dry location

 CCT (K)
 3000K

 CRI
 90

Optical

Lighting type Direct
LED type Power LED
Light distribution Symmetric
Optical type Spot
Beam angle (°) 10
Beam angle C90-270 (°) 10



Luminous flux luminaire 2888 lm (EXTREME CUT OFF)

Beam Angle:			10°
h(m)		E(lx)	D(m)
1_	50870		0.18
2	1:	2718	0.36
3	5652		0.55
4	3179		0.73
5	5 2035		0 91



63x433









Electrical

 Frequency (Hz)
 50/60

 Voltage (V)
 220.00

 Dimmable
 Yes

 Driver
 Remote included

 Driver type
 Dimmable DALI

Emergency Insulation class

Without II

Physical

 Color
 White/Chrome
 Tilt (°)
 30

 Orientation
 Adjustable
 Length (mm)
 436

 Trim
 yes

 Recessed depth (mm)
 75

0.66

Note

Weight (kg)

Pre-Installation frame not required.