




Light Shadow Adjustable Trim Dali Version 12 Spots Optic Wide Flood

03.7327.40ADA - White/Gold

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V).




Main specifications

Number of heads	1	Net lumen (lm)	2597
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	32.4W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	46
Beam angle C90-270 (°)	46



Beam Angle: 46°

h(m)	E(lx)	D(m)
1	4784	0.84
2	1196	1.69
3	532	2.53
4	299	3.38
5	191	4.22

Luminous flux luminaire
2597 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Remote included		
Driver type	Dimmable DALI		
	1		

Physical

Color	White/Gold	Tilt (°)	30
Orientation	Adjustable	Length (mm)	436
Trim	yes		
Recessed depth (mm)	75		
Weight (kg)	0.66		

Note

Pre-Installation frame not required.

